

BC-PDR-500K Android Smart Computer

BC-PDR-500K serial products extend Handheld-Wireless product series into Android OS 5.1.1 handheld terminal with numeric keypad. Inside the compact terminals, sealing level of IP65 water/dust proof, 1.5m/4.5ft drop survival, ergonomic design, over-molding structure, and 4.0 inch tough screen are all equipped to ensure performance. Latest 1.3GHz quad-core processor 2GB RAM/16GB ROM and up to 32GB expansion are all designed to boost up experience level.



FEATURES & BENIFITS

High Speed Data Communication

Double insurance of 4G high Speed network and dual-frequency WIFI network can ensure the real-time data communication in different using environment;

Extraordinary Battery Life

Extremely battery of 5200mAh can ensure long battery in different using environment;

Rugged Ergonomic and Over-molding Design

Over-molding and ergonomic hardware design can satisfy most of the tough environment from different fields;

Extremely Stable Hardware Display

4.0 inch tough screen can ensure the performance under different tough environment;

Highly Customized Structure

'All-in-One' hardware design conception can expand the hardware module integration based on different project requirements, especially like UHF+HF, UHF+LF, LF+HF;

High Efficiency Operating

Numeric keypad can ensure the high efficiency operating status;

Quick-Charging



31% smaller and lighter than leading devices in the rugged class.



Android 5.1 Lollipop operating systems for flexible application support and migration.



5ft./1.5 m drop to concrete across the operating temperature range)



Industry's fastest and farthest imaging engines deliver superior motion tolerance and barcode read performance.

Quick-charging technology can provide the most efficient experience;

Perfect Service

Professional and skillful service involving the whole life cycle can guarantee the stability.

SPECIFICATIONS		
PHYSICAL CHARACTERISTICS		
Dimension	158mm(H)x75mm(W)x28mm(D)±2 mm	
Weight	Net Weight :300g (including battery&wrist strap)	
Display	4.0 in. TFT-LCD(WVGA 480x800)touch screen with backlight	
Backlight	LED backlight	
Keypads	3 TP keys, 17 function keys, 4 side buttons	
Expansions	2 PSAM, 1 SIM, 1 TF	
Battery	Rechargeable li-ion polymer, 3.7V, 5200mAh	
PERFORMANCE CHARACTERSTICS		
CPU	Quad A53 1.3GHz quad-core	
Operating System	Android 5.1.1	
Storage	2GB RAM, 16GB ROM, MicroSD(max 32GB expansion)	
USER ENVIRONMENT		
Operating Temp.	-20°C to 50°C	
Storage Temp.	-20°C to 70°C	
Humidity	5%RH to 95%RH(non-condensing)	
Drop Specifications	5ft./1.5 m drop to concrete across the operating temperature range	
Sealing	IP65, IEC compliance	
ESD	±15kv air discharge, ±8kv direct discharge	
DEVELOPMENT ENVIRONMENT		
SDK	HHW Software Development Kit	
Language	Java	
Environment	Android Studio or Eclipse	
DATA COMMUNICATION		
WWAN	TDD-LTE Band 38, 39, 40, FDD-LTE Band 1, 2, 3, 4, 7; WCDMA(850/1900/2100MHz); GSM/GPRS/Edge 850/900/1800/1900MHz)	
WLAN	2.4GHz/5.8GHz Dual Frequency, IEEE 802.11 a/b/g/n/ac	
WPAN	Bluetooth Class v2.1+EDR, Bluetooth v3.0+HS, Bluetooth v4.0	
GPS	GPS(embedded A-GPS), accuracy of 5 m	
DATA CAPTUER		
BARCODE READER(OPTIONAL)		
1D barcode	1D laser engine	Symbol SE955

	Symbologies	All major 1D barcodes
2D barcode	2D CMOS Imager	Honeywell N6603
	Symbologies	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode, Postal Codes, US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal. etc.
COLOR CAMERA		
Resolution	8.0 megapixel	
Lens	Auto-focus with LED flash	
RFID READER(OPTIONAL)		
RFID LF	Frequency	125KHz/134.2KHz(FDX-B/HDX)
	Protocol	ISO 11784&11785
	R/W Range	2cm to 10 cm
RFID HF	Frequency	13.56MHz
	Protocol	ISO 14443A&15693
	R/W Range	2cm to 8cm
Active 2.45GHz	Read range more than 200 m	
433MHz	Read range more than 200 m	
PSAM SECURITY(OPTIONAL)		
Protocol	ISO 7816	
Baudrate	9600, 19200, 38400,43000, 56000, 57600, 115200	
Slot	2 slots(maximum)	
ACCESSORIES		
Standard	1xPower Supply 1xLithium Polymer Battery 1xDC charging cable 1xUSB data cable	
Optional	Magnetic charging cable	