

BC-95AC

Black Copper Thermal Receipt Printer



Features

- Horizontal, Wall-hanging design.
- Easy of use feature include drop in paper load and auto cutter.
- Flexibility interface include USB+Serial, ethernet option.



Specification

Printing

Printing method	Direct thermal
Print width	72mm
Column capacity	576 dots/line 512 dots/line
Printing speed	200mm/s
Interface	USB+Serial / Lan
Printing paper	79.5±0.5mm
Line spacing	3.75mm (Adjustable by commands)
Character size	ANK, Font A : 1.5×3.0mm(12×24 dots) Font B : 1.1×2.1mm(9×17 dots)Chinese, traditional Chinese:3.0×3.0mm(24×24 dots)

Cutter

Auto cutter	Partial
-------------	---------

Power

Power adaptor	Input : AC 110V/220V, 50~60Hz
Power source	Output : DC 24V/2.5A
Cash drawer output	DC 24V/1A

Physical characteristics

Weight	1.0 KG
Dimensions	183.3 ×140×141.5 mm (D×W×H)
Environmental Requirements	
Work environment	Temperature (0~45) humidity(10~80%)
Storage environment	Temperature(-10~60℃) humidity(10~80%)

Reliability

Cutter life	1.5 million cuts
Printer head life	100KM