

BC-98AC

Black Copper Thermal Receipt Printer



Features

- 200mm/s high printing speed.
- ESC/POS compatible, setting DIP switch to choose characters and fonts.
- Better sealing performance for mechanism and printer, Mechanism life can reach to 100km and Auto cutter life with 1.5 million cuts.



Specification

Printing

Printing method	Direct thermal
Print width	72mm
Column capacity	576 dots/line 512 dots/line
Printing speed	200mm/s
Interface	USB+Serial / Lan
Printing paper	79.5±0.5mm
Line spacing	3.75mm (Adjustable by commands)
Character size	ANK, Font A : 1.5×3.0mm(12×24 dots) Font B : 1.1×2.1mm(9×17 dots)Chinese, traditional Chinese:3.0×3.0mm(24×24 dots)

Cutter

Auto cutter	Partial
-------------	---------

Power

Power adaptor	Input : AC 110V/220V, 50~60Hz
Power source	Output : DC 24V/2.5A
Cash drawer output	DC 24V/1A

Physical characteristics

Weight	1.0 KG
Dimensions	183.3 ×140×141.5 mm (D×W×H)
Environmental Requirements	
Work environment	Temperature (0~45) humidity(10~80%)
Storage environment	Temperature(-10~60℃) humidity(10~80%)

Reliability

Cutter life	1.5 million cuts
Printer head life	100KM