



# 1215L 12.1-inch LCD

Touchscreen Monitor



**Integrated Touch**



**Commercial Grade**



**3-Year Warranty**

## Product Overview

The Elo 1215L 12.1-inch standard format touchscreen monitor is designed for touch with proven Elo expertise and reliability built in. Available with two touch technology options, both offer a sleek bezel design with responsive single touch capability. AccuTouch® five-wire resistive technology, the most widely used for retail applications, supports touch sensitivity for fingernails, gloves, credit cards, or any stylus enabling you to capture signatures or touch with precision. IntelliTouch® surface acoustic wave (SAW) delivers superior image quality and support for finger or glove touch modes.

Multiple mounting options are available to ensure installation flexibility including: wall and pole-mount via standard VESA mount patterns as well as tabletop accommodations with the use of the desktop stand.

**Available with single touch AccuTouch five-wire resistive technology or IntelliTouch surface acoustic wave technology (SAW)**

**Touchscreen sealed against spills**

**Removable base and VESA mounting option**

## 1215L 12.1-inch Touchscreen Monitor

Specifications	
Model	1215L
Color	Dark gray
Active Display Area	9.69" x 7.27" (246mm x 184.5mm)
Dimensions	11.86" x 11.26" x 6.61" (300.93mm x 285.85mm x 167.69mm)
Diagonal	12.1"
Aspect Ratio	4:3
Native Resolution	800 x 600 @ 56, 60, 70 or 75 Hz
Other Supported Resolutions	640 x 480 @ 60, 66 Hz (Mac), 72 or 75 Hz
Number of Colors	262,000
Number of Touches	Single-touch
Brightness (typical)	LCD panel: 200 nits; with AccuTouch: 164 nits; with IntelliTouch: 184 nits
Response (typical)	35 msec (typical)
Viewing Angle	Horizontal (left/right): ±70° or 140° total; Vertical (up/down): 50° or 100° total
Contrast Ratio	500:1 (typical)
On-Screen Display	OSD buttons: menu, up, down, select, power OSD: contrast, brightness, H/V position, recall default, RGB (color temp), OSD exit, clock, phase, sharpness, OSD H/V position, OSD time, auto adjust, language (English, German, Spanish, Japanese, French), input select OSD disable/enable: power, OSD menu
Input Video Format	Analog VGA
Input Video Signal Connector	Mini D-Sub 15-Pin VGA type
Input Frequency	Horizontal: 31.5-48 kHz; Vertical: 56.3-75 Hz
Power	Type: Internal, with jack to accept power from optional external brick AC Input (line) voltage: 85-265 VAC, 47-63 Hz DC Input (line) voltage: 12.0 V ± 0.75V
Power Consumption	16W
Shipping Dimensions	14.77" x 10.24" x 14.38" (375mm x 260mm x 365mm)
Temperature	Operating: 0°C to 40°C; Storage: -20°C to 60°C
Humidity	Operating: 20%-80%; Storage: 10%-90% noncondensing
Weight	Actual: 7.92 lb (3.59 kg); Shipping: 13.2 lb (5.99 kg)
Mounting Options	Threaded-through mounting holes, under base; Removable base; 75 mm VESA mount
Regulatory Approvals & Declarations	UL/cUL, TÜV-GS, CE, FCC/IC/VCCI/C-Tick Class B
Warranty	3 years
MTBF	50,000 hours demonstrated
What's in the Box	QIG, User Manual CD, VGA cable, serial cable (attached if support combo), power cord(s), USB cable

## Ordering Information

Model	Part Number	Technology	Interface	Surface Treatment	Availability
1215L	E432532	AccuTouch	Serial/USB	Anti-Glare	Worldwide
	E991639	IntelliTouch	Serial/USB	Anti-Glare	Worldwide

## Extended Warranty Options

Part Number	Description
758588-000	1 Year Extended Warranty, 7-inch to 22-inch LCD Touchmonitor
930057-000	2 Year Extended Warranty, 7-inch to 22-inch LCD Touchmonitor
E67295-000	Elo advance unit replacement for touchmonitors

To find out more about our extensive range of Elo touch solutions, go to [elotouch.com](http://elotouch.com), or call the office nearest you.

### North America

Tel +1 408 597 8000  
Fax +1 408 597 8050  
[elosales.na@elotouch.com](mailto:elosales.na@elotouch.com)

### Europe

Tel +32 (0)16 70 45 00  
Fax +32 (0)16 70 45 49  
[elosales@elotouch.com](mailto:elosales@elotouch.com)

### Asia-Pacific

Tel +86 (21) 3329 1385  
Fax +86 (21) 3329 1400  
[www.elotouch.com.cn](http://www.elotouch.com.cn)

### Latin America

Tel +1 786-923-0251  
Fax +1 305-931-0124  
[www.elotouch.com](http://www.elotouch.com)

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo, AccuTouch and IntelliTouch are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2017 Elo Touch Solutions, Inc. All rights reserved. 17011AES00063

