



## BC-24GSL3-10G-F410G

### 10G uplink 24 Port Gigabit Layer 3 Managed Switch

24X1000Mbps RJ45 + 4X1000Mbps SFP (combo)+ 4X10G Mbps SFP + Console



## Overview

The BC-24GSL3-10G-F410G Layer 3 Managed Switch is designed for Small and Medium Enterprises (SMEs), Large Enterprises and Internet Service Providers (ISPs). They offer high performance, flexibility, fault tolerance and advanced software features for maximum return on investment. The BC-24GSL3-10G-F410G switch features Gigabit Ethernet RJ45 and SFP ports, 10 GbE SFP+ ports, advanced security features and advanced Quality of Service (QoS) and can be used as a core, distribution or access layer switch with high port Density, switch stacking and ease of management, ideal for a variety of commercial networking applications.

# Features

## Port 6KV lightning protection, dual power redundant design

- All ports support 6KV lightning protection.
- Dual power redundant design, support seamless switchover in case of failure without manual intervention.

## Advanced hardware architecture design, powerful processing capability

- Using high-performance switching chips, it can meet the application requirements of various complex scenarios and greatly improve the network data processing rate.

## Powerful business processing capabilities

- Support 802.1Q VLAN, MAC VLAN, IP VLAN, users can flexibly divide VLAN as needed.
- Support QoS, 8 port queues, support port priority, 802.1P priority, DSCP priority, support SP, WRR, SP+WRR, WFQ priority scheduling algorithm.
- Support ACL, support L2 (Layer 2) ~ L4 (Layer 4) packet filtering function, provide flexible and secure access control policy.
- Support IGMP v1/v2/v3 Snooping, MLD v1/v2 Snooping, to meet the requirements of multi-terminal HD video surveillance or video conference.
- Supports the fast leave mechanism and querier of Layer 2 multicast, supports Layer 2 IPv4 static multicast and Layer 2 IPv6 static multicast.
- Support RIP dynamic routing protocol, solve the routing problem after the small and medium-sized network is divided into subnets, and simplify the network configuration.
- Support static routing protocol, and manually configure routing entries to realize communication between different network segments.
- Support proxy ARP, so that hosts in different physical networks on the same network segment can communicate normally.

## Perfect security mechanism

- Complete security authentication mechanism: It supports IEEE 802.1x, Radius, Tacacs+, etc., and can provide users with a complete security authentication mechanism.
- The perfect loop detection mechanism can ensure the stable operation of the network for a long time.
- Provide port isolation in the same VLAN, and security features such as DHCP-Snooping, IP+MAC+port binding, etc., to further ensure user data security.
- Support ARP protection, IP source protection, DoS protection.
- Support to restrict user access based on port number, IP address, and MAC address.

## Diverse reliability protection

- Support STP (IEEE 802.1d), RSTP (IEEE 802.1w) and MSTP (IEEE 802.1s) protocols to eliminate Layer 2 loops and implement link backup.
- Supports loop protection, root bridge protection, TC protection, BPDU protection, and BPDU filtering.
- Support 50ms switching of optical ports.

## Flexible and convenient management and maintenance

- Support various management methods such as Console, Telnet, and SSH.
- Support WEB management (HTTP, HTTPS, SSL V3), which is simpler and more efficient, and is convenient for users to install and debug.
- Support file upload and download management in TFTP mode.
- Support SNMP V1/V2/V3 to facilitate device management through the network management platform.
- Support one-stop management and maintenance of Fengrunda Apollo cloud platform, which can realize all-round remote operation and maintenance such as automatic device discovery, network topology management, and remote configuration management of devices.

# Specifications

Hardware Specifications	
Network Interface	<ul style="list-style-type: none"><li>• 24 10/100/1000Mbps RJ45 Port</li><li>• 4 10G SFP+ Port</li><li>• 4 Gigabit SFP Port(Combo)</li><li>• 1 RJ45 Console Port, 1 10/100Mbps RJ45 managed Port</li><li>• 1 USB 2.0 interface,1 Mini-usb Console</li></ul>
Network protocol standard	<ul style="list-style-type: none"><li>• IEEE 802.3、IEEE 802.3i、IEEE 802.3u、IEEE 802.3ab、IEEE 802.3z、IEEE 802.3ad、IEEE 802.3x、IEEE 802.1p、IEEE 802.1q、IEEE 802.1d、IEEE 802.1s、IEEE 802.1w</li></ul>
Performance Specifications	<ul style="list-style-type: none"><li>• Backplane bandwidth: 128Gbps</li><li>• Packet forwarding rate: 95.2Mpps</li><li>• MAC address table: 16K</li><li>• Port cache: 12Mb</li><li>• Forwarding Mode: Store and Forward</li></ul>
LED indicator	<ul style="list-style-type: none"><li>• 321000M Link/Act indicators</li><li>• 24 10/100Mbps Link/Act indicators</li><li>• 1 Power indicator</li><li>• 1 SYS indicator</li></ul>
Power support	<ul style="list-style-type: none"><li>• Input power: AC 100-240V/50-60Hz</li><li>• Dual power redundant input</li></ul>
Physical Specifications	<ul style="list-style-type: none"><li>• Dimensions (LxWxH): 440mm×320mm×44mm</li></ul>
Environmental Specifications	<ul style="list-style-type: none"><li>• Working temperature: 0°C~40°C</li><li>• Storage temperature: -40°C ~ 70°C</li><li>• Working humidity: 10%~90% RH non-condensing</li><li>• Storage humidity: 5%~90% RH non-condensing</li></ul>
Safety regulations	<ul style="list-style-type: none"><li>• CE/ROHS/FCC</li></ul>