

BC-100AC

Black Copper Thermal Receipt Printer



Features

- Unique patient design
- Easy paper loading
- Horizontal, Wall-hanging design.
- Easy of use feature include drop in paper load and auto cutter.
- Flexibility interface include Serial, USB, Ethernet.

Specification

Printing method	Direct Thermal
Printing Speed	300mm/s
Resolution	8 dots/mm, 576 dots/line
Effective Printing Width	72mm
Character Set	95 Alphanumeric, 18 set International
Print Font	Alphanumeric, Chinese
Character per Line	48-font A/64-font B
Standard	Paper out, Cover open, Cutter jam
Paper Type	Thermal paper
Paper Width	79.5± 0.5mm
Paper Roll Diameter	Max: 80.0mm
Roll Core Inner Diameter	(13mm(min))
Paper Thickness	0.06 to 0.07mm Drop-in paper load
MCBF	60 million lines
Auto Cutter	500,000 cuts (Partial/Ful)
Barcode	UPC-A, UPC-E, EAN-8, EAN-13, CODE 39 ITF, CODBAR, CODE 128, CODE 93, QR, PDF417
TPH	150km
Windows	2000/XP/VISTA/LINUX/7/8/10/11
Interface	USB, Serial, Ethernet
Power	AC100 ~240V(± 10%) DC 24V, 2A
Cutter Life	3,000,000 cuts
Net Weight	1.3kg
Gross Weight	2.8kg
Printer Dimension	(WxLxH) 145 x 195x 148 mm