

BC-5404UR-WM

4U Wall Mounted Cabinet



Standard

Comply with ANSI/EIA RS310-D, DIN41497 part 1, IEC297-2, DIN41494 part 7, GBIT3047.2-92 standard.

Feature

19 inch standard;

Removable Side Panels side locks are optional;

Knock-off hole for entering cable on both top cover, bottom panel, rear panel

Turning angle of front door is over 180 degrees

Easy mounting installation

Unassembled package saving shipping space

Fans, shelf and PDU are optional

Loading Capacity

30KGS

Degree of Protection

IP20

Material

SPCC Cold Rolled Steel

Thickness: 1.0mm-0.6mm

Surface Finish:

Powder coating

Cabinet details



Holes for wall mounting



Bottom



Removable side panels (Side lock optional)



Cable entrance on rear panel



The glass door with blue strips



Zinc plated mounting profile with U mark (Ground wire optional)

Main Parts

S/N	Specification	Quantity	Unit	Material	Surface Finish	Remark
1	Mounting profile	4	Piece	Coated Zinc plate t1.0	Coated Zinc	
2	Frame	2	Piece	SPCC cold rolled steel t0.6	Powder coated	
3	Side panel	2	Piece	SPCC cold rolled steel t06	Powder coated	
4	Top cover	1	Piece	SPCC cold rolled steel t06	Powder coated	
5	Bottom panel	1	Piece	SPCC cold rolled steel t06	Powder coated	
6	Rear panel	1	Piece	SPCC cold rolled steel t06	Powder coated	
7	Front door	1	Piece	Toughened glass 4.5mm	Powder coated	
8	Lock	1	Piece	Steel	Color Zinc	with 2 keys
9	M6 Square nut	12	Piece	Steel	Color Zinc	
10	M6 B-head screw	12	Piece	Steel	Color Zinc	
11	Allen wrench	1	Piece	Steel	Color Zinc	

Specification

Model No.	Capacity	Width	Depth	Height	Packing dimension	Volume
	(U)	(mm)	(mm)	(mm)	(mm)	(CBM)
BC-5404UR-WM	4	542	400	280	565*425*145	0.035

Color

RAL9004	RAL7035
black	grey
	