

# BC-6412UR-WM

## 12U Single Section Wall Mounted Cabinet



### Standard

Comply with ANSI/EIA RS310-D, DIN41497 part 1, IEC297-2, DIN41494 part 7, GBIT3047.2-92 standard.

### Feature

- 19 inch standard;
- Removable Side Panels side locks optional;
- Knock off hole for entering cable on both top cover, bottom panel, real panel
- Turning angle of front door is over 180 degrees
- Easy mounting installation
- Unassembled package saving shipping space
- fans, shelf, PDU are optional

### Loading Capacity

60KG

### Degree of Protection

IP20

### Material


SPCC Cold Rolled Steel

Thickness: 1.5mm-1.0mm-0.8mm


### Surface Finish:

Powder coating

### Cabinet details



Fan exhaust hole



Bottom



Removable side panels (Side lock optional)



Cable entrance on rear panel



Front tempered glass door with metal perforated border



Zinc plated mounting profile with U mark (Ground wire optional)

# WS Single Section Wall Mounted Cabinets

## Main Parts

S/N	Specification	Quantity	Unit	Material	Surface Finish	Remark
1	Mounting profile	4	Piece	Coated Zinc plate t1.5	Coated Zinc	with U mark
2	Frame	2	Piece	SPCC cold rolled steel t10	Powder coated	
3	Side panel	2	Piece	SPCC cold rolled steel t0.8	Powder coated	
4	Top cover	1	Piece	SPCC cold rolled steel t0.8	Powder coated	
5	Bottom panel	1	Piece	SPCC cold rolled steel t0.8	Powder coated	
6	Rear panel	1	Piece	SPCC cold rolled steel t0.8	Powder coated	
7	Front door	1	Piece	5MM toughened glass door/SPCC t1.0	Powder coated	
8	Lock	1	Piece	Steel	Color Zinc	with 2 keys
9	M6 Square nut	12	Piece	Steel	Color Zinc	
10	M6 B-head screw	12	Piece	Steel	Color Zinc	
11	Allen wrench	1	Piece	Steel	Color Zinc	

## Specification

Model No.	Capacity	Width	Depth	Height	Packing dimension	Volume
	(U)	(mm)	(mm)	(mm)	(mm)	(CBM)
BC-6412UR-WM	12	600	450	635	665*595*236	0.093

## Color

RAL9004	RAL7035
black	grey
