

# BC-6609UR-WM

## 9U Single Section Wall Mounted Cabinet



### Standard

Comply with ANSI/EIA RS310-D, DIN41497 part 1, IEC297-2, DIN41494 part 7, GB/T3047.2-92 standard.

### Feature

19 inch standard;

Removable Side Panels side locks optional;

Knock off hole for entering cable on both top cover, bottom panel, rear panel

Turning angle of front door is over 180 degrees

Easy mounting installation

Unassembled package saving shipping space

Fans, shelf, PDU are optional

### Loading Capacity

60KG

### Degree of Protection

IP20

### Material


SPCC Cold Rolled Steel

Thickness: 1.5mm-1.0mm-0.8mm

### Surface Finish:

Powder coating

### Cabinet details



Fan exhaust hole



Bottom



Removable side panels  
(Side lock optional)



Cable entrance on rear panel



Front tempered glass door  
with metal perforated border



Zinc plated mounting  
profile with U mark  
(Ground wire optional)

# WS Single Section Wall Mounted Cabinets

## Main Parts

S/N	Specification	Quantity	Unit	Material	Surface Finish	Remark
1	Mounting profile	4	Piece	Coated Zinc plate t1.5	Coated Zinc	with U mark
2	Frame	2	Piece	SPCC cold rolled steel t10	Powder coated	
3	Side panel	2	Piece	SPCC cold rolled steel t0.8	Powder coated	
4	Top cover	1	Piece	SPCC cold rolled steel t0.8	Powder coated	
5	Bottom panel	1	Piece	SPCC cold rolled steel t0.8	Powder coated	
6	Rear panel	1	Piece	SPCC cold rolled steel t0.8	Powder coated	
7	Front door	1	Piece	5MM toughened glass door/SPCC t1.0	Powder coated	
8	Lock	1	Piece	Steel	Color Zinc	with 2 keys
9	M6 Square nut	12	Piece	Steel	Color Zinc	
10	M6 B-head screw	12	Piece	Steel	Color Zinc	
11	Allen wrench	1	Piece	Steel	Color Zinc	

## Specification

Model No.	Capacity	Width	Depth	Height	Packing dimension	Volume
	(U)	(mm)	(mm)	(mm)	(mm)	(CBM)
BC-6609UR-WM	9	600	600	501	635*635*231	0.093

## Color

RAL9004	RAL7035
black	grey
