

BC-6632UR-FS

32U Floor Standing Server Rack





Standard

Comply with ANSI/EIA RS-310-D, DIN41497 part 1, IEC297-2, DIN41494 part 7, GBIT3047.2-92 standard.

Feature

19 inch width standard;

Removable Side Panels, side locks optional;

Knock off hole for entering cable on both top cover, bottom panel, real panel

Turning angle of front door is over 180 degrees

Easy mounting installation

Unassembled package saving shipping space

fan, shelf, PDU are optional

Loading Capacity

800KG

Degree of Protection

I P20

Material

SPCC Cold Rolled Steel

Thickness:2.0mm-1.2mm-1.0mm

Surface Finish:

Powder coating

Cabinet details



Handle lock

Fan group optional



Zinc plated mounting profile



Cable entrance on rear panel



Removable side panels (Side lock optional)



Ground wire optional

Specification

Model No.	Capacity	Width	Depth	Height	Volume	Standard accessories
	(U)	(mm)	(mm)	(mm)	(CBM)	
BC-6632UR-FS	32	600	600	1609	0.186	2 fans + 1 shelf

Main Parts

S/N	Specification	Quantity	Unit	Material	Surface Finish	Remark
1	Frame	2	Piece	SPCC cold rolled steel t1.0	Powder coated	
2	Side panel	2	Piece	SPCC cold rolled steel t1.0	Powder coated	
3	Top cover	1	Piece	SPCC cold rolled steel t1.2	Powder coated	
4	Bottom panel	1	Piece	SPCC cold rolled steel t1.2	Powder coated	
5	Mounting profile	4	Piece	SPCC cold rolled steel t2.0	Zinc plated	
6	Mounting rail	4/6	Piece	SPCC cold rolled steel t1.2	Powder coated	
7	Front door	1	Piece	5MM toughened glass door/SPCC t1.2	Powder coated	
8	Back door	1	Piece	Single open mesh vented door t1.2	Powder coated	
9	Castors	4	Piece			
10	Leveling feet	4	Piece			
11	Lock	2	Piece			with 2 keys
12	M6 Square nut	30	Piece	Steel	Color Zinc	
13	M6 B-head screw	30	Piece	Steel	Color Zinc	
14	Allen wrench	1	Piece	Steel	Color Zinc	


Definition of door

black

Model No.	Front door		Rear doo	r	
FS	Toughened glass door with round vented border(Handle Lock)	.			
FS-M	Toughened glass door (small round lock)	Solid metal d	oor(small roun	d lock)	
FP	Mesh vented door	Mesh vented	door(small rou	und lock)	
Remark:If choose	split rear door will use handle lock	Definition of Orna for toughened gla			
RAL9004	RAL7035	Blue	Red		

RAL7035
grey

Unassembled packing details(2-4 cartons)



carton 1:top cover+bottom panel+1 shelf carton 3:extra shelf if needed



carton 2frame+mouting profile+door+side panel carton 4:vertical management if needed