

Product datasheet

Specifications

Cat6 Patch Cord UTP 5M CM, Blue

ACTPC6UBCM50BU



⚠ Discontinued on: 20-Nov-2020

⚠ End-of-service on: 31-Dec-2020

⚠ Discontinued

Main

range	Actassi
product	Patch cord
Colour	Blue
Cable shielding type	UTP

Complementary

Type of cable	4 pair cables
Rated voltage	150 V AC
[In] rated current	1.5 A
Insulation resistance	500 MOhm
length (customizable value in configurator)	0...5 m
Communication network category	6
Contacts material	Phosphor bronze with 50 micro-inches gold over 100 micro-inches nickel
Contact resistance	10 mOhm
AWG gauge	AWG 24
Attenuation	Guaranteed: 0.1 dB
Far end crosstalk [FEXT]	49.8 dB
Power sum far end crosstalk [PSFEXT]	46.9 dB
Minimum number of matings	1000 cycles
targeted region	Asia Pacific.

Environment

Flame retardance	CM
Standards	IEC 60603-7 FCC part 68 Subpart F AS/NZS 3080:2003 TIA/EIA-568-B ISO/IEC 11801 2nd edition

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Package 1 Height	0.008 cm
Package 1 Width	21 cm
Package 1 Length	30.2 cm
Package 1 Weight	216 g

Contractual warranty

Warranty	18 months
-----------------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better

Materials and Substances

[China RoHS Regulation](#)

[China RoHS declaration](#)

Use Again

Repack and remanufacture

[Circularity Profile](#)

[No need of specific recycling operations](#)

[WEEE](#)



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins